

## IN THE ABSTRACT

Please amend the abstract as follows:

~~For producing a longitudinal connection seam an~~ An installation device connects ~~for connecting~~ shell-shaped longitudinal segments of a jacket body, ~~that forms a large component determines a hollow space with an open face, comprises at~~ At least one tool pair ~~which~~ comprises an inner tool that is movably guided within ~~[[the]]~~ a hollow space in longitudinal direction of the jacket body~~[[.]]~~ and ~~further comprises~~ an outer tool that is movably guided outside the hollow space defined in longitudinal direction, ~~wherein the~~ The tools act together as a tool pair ~~in the direction across the longitudinal direction of the body~~. The installation device comprises a carrier pair which is formed by an inner guide carrier that extends in a longitudinal direction and movably guides the inner tool within the hollow space ~~of the jacket body~~, and ~~further comprises~~ an outer guide carrier that extends in longitudinal direction outside the jacket body and movably guides the outer tool. Each guide carrier is rotatably held and fastenable according to at least one ~~longitudinal~~ rotary axis oriented ~~by the~~ to an outer ~~longitudinal~~ contour of the jacket body, as well as being slidably held and fastenable in at least two separate spatial directions that extend across the longitudinal direction of the body, such that the tools acting together as a pair selectively take up different positions on the longitudinal circumference of the jacket body.